



BRIXTON FLASH

<https://polstar.com.pl/ru/produkt/spodnie-do-pasa-krotkie>



□□□□□□: □□□□□□□□□□ □ □ □□□□□□□□□□
□□□□□□□□, □□□□□□ □□□□□□□□□□□□□□□□
□□□□□ □ □□□□□□□□ □□□□□□□□□□□□□□□□,
□□□□□/□□□□□: □□□□□□□□□□□□, □□□□□□ □ □□□□□
□□□□□, □□□□□ □□□□□□□□, □□□□□□□□□□□□□□□□
□□□□□ □ □□□□□□, □□□□□□□□□□□□□□□□
□□□□□□□□, □□□□□ □□□□□□□□□□□□, □□□□□ □□
□□□□□□□□,
□□□□□□: □□□□□ □ □□□□ □□□□□□□□ □ □□□□
□□□□□ □□□□□□□□□□ □ "□□□□□□", □□□□□□□□
□□□□□□, □□□□□ □□□□□□□□□□□□,
□□□□□□□□□□□□□□□□: □□□□□□□□□□□□□□,
□□□□□□□□□□□□□□: □□□□□□□□□□□□□□

BRIXTON- FLASH®

Symbol:	Polstar Holding Wołoszczuk sp.k.
Waga:	AFKS
Wysokość:	260 g/m ²
Przepuszczalność:	0000000/000000000000
Przepuszczalność (55%/45%):	(55%/45%)
Wymiary:	000000 000000000000 00000000
Norm:	EN ISO 13688:2013, EN ISO 20471:2013/A1:2016,
Wysokość:	10
Kolorystyka:	

WYMIARY			SIZE
□□□□	□□□□□	□□□□□□	
164-170	088-092	080-084	46
170-176	096-100	088-092	50
170-176	092-096	084-088	48
176-182	100-104	092-096	52
176-182	104-108	096-100	54
182-188	108-112	100-104	56
182-188	112-116	104-108	58
188-194	116-120	108-112	60
188-194	120-124	112-116	62
194-200	124-128	116-120	64

GO FOR MORE!
naprzód po więcej! www.consumo.com.pl